

e-2-s v2

Dynamic Email to SMS Gateway

DYNAMICAL CONVERTING OF EMAILS TO SMS

- ✓ Working out of the box – **NO software required**
- ✓ Supports **Email-Server-Mode** and **Email-Client-Mode** simultaneously
- ✓ **HTTP REST API** for sending SMS
- ✓ Periodical **Heart Beat SMS**
- ✓ **SMS to Email**
- ✓ Alarm-Email & SMS-Logfile
- ✓ Phone book with 200 recipients
- ✓ Multi-Part SMS
- ✓ Email-Subject & Email-Body support
- ✓ Operates in your internal LAN or without LAN via 2G/3G/4G-LTE (DUAL-SIM fail-over switching)
- ✓ Robust metal-housing
- ✓ Content of package:
 - e-2-s v2 Gateway
 - Printed starting-guide
 - DIN- & wall-mounting clip
 - Option: 19"-mounting-kit



TECHNICAL PARAMETERS

Mobile Interface	LTE: 150 Mbps (DL) / 50 Mbps (UL) 3G: 42 Mbps (DL) / 5,76 Mbps (UL) 2G: 237 kbps (DL) / 59,2 kbps (UL)	
Temperature range	Function Storage	-40° C to + 75°C -40° C to + 85°C
I/O Interface	1x Digital input 1x Digital output	
Supply voltage	9 to 36 VDC	
Consumption	Idle Average	2,5 W 4 W
Dimensions	Metal Housing	31,2 x 94 x 129 mm (DIN 35 mm)
Antenna connector	2x SMA - female – 50 Ohm	
Network interface	2x ETH	Ethernet (10/100 Mbit/s)
Frequency bands	LTE-FDD: 700/800/900/1800/2100/2600 MHz LTE-TDD: 2300, 2500, 2600 MHz UMTS/HSPA+: 900/2100 MHz GSM/GPRS/EDGE: 900/1800 MHz	

