

e-2-s

Dynamic Email to SMS Gateway



DYNAMICAL CONVERTING OF EMAILS TO SMS

- ✓ Working out of the box – **NO software required**
- ✓ Supports **Email-Server-Mode** and **Email-Client-Mode** simultaneously
- ✓ **Heart Beat SMS**
- ✓ **SMS to Email**
- ✓ Alarm-Email & SMS-Logfile
- ✓ Phone book with 50 recipients
- ✓ Parallel Operation Modes:
 - Fully dynamic (Keyword based)
 - Half dynamic (Rule based)
- ✓ Operates in your internal LAN or even without existing LAN through mobile-data-connection on 2G/3G (fail-over switching possible)
- ✓ Version in plastic-housing or robust metal-housing available
- ✓ Content of package:
 - e-2-s Gateway
 - Power supply
 - Magnetic antenna (2m cable)
 - Stick antenna
 - Crossover UTP cable
 - Clip for the DIN rail-mounting
 - Printed starting-guide



TECHNICAL PARAMETERS

Complies with standards	EN 301 511, v9.0.2 ETSI EN 301 489-1 V1.9.1 EN 60950-1:06 ed.2 + A11:09 + A1:10	
Temperature range	Function Storage	-40° C to + 70°C -40° C to + 85°C
Protection	Freely In switch board	IP20 IP56
Supply voltage	10 to 30 V DC	
Consumption	Reception Transmission	2,3 W 5,5 W
Dimensions	Plastic box Metal box	51 x 87 x 116 mm (DIN 35 mm) 42 x 87 x 113 mm (DIN 35 mm)
Antenna connector	SMA – 50 Ohm	
User interface	2x ETH	Ethernet (10/100 Mbit/s)
Frequency bands	GSM/GPRS/EDGE: Quad band, 850/900/1800/1900 MHz UMTS/HSDPA/HSUPA/HSPA+: Five band, 800/850/900/1900/2100 MHz	

Der Niederösterreichische
Innovationspreis

