

# e-2-s

## Dynamic Email to SMS Gateway



### DYNAMICAL CONVERTING OF EMAILS TO SMS

- ✓ Working out of the box – **NO software required**
- ✓ Supports **Email-Server-Mode** and **Email-Client-Mode** simultaneously
- ✓ **Heart Beat SMS**
- ✓ **SMS to Email**
- ✓ Alarm-Email & SMS-Logfile
- ✓ Phone book with 200 recipients
- ✓ Multi-Part SMS
- ✓ Email-Subject & Email-Body support
- ✓ Operates in your internal LAN or without existing LAN through 2G/3G/4G-LTE connection (DUAL-SIM fail-over switching)
- ✓ Version in plastic-housing or robust metal-housing available
- ✓ Content of package:
  - e-2-s Gateway
  - Power supply
  - 2 LTE-antennas
  - Crossover UTP cable
  - Clip for the DIN rail-mounting
  - Printed starting-guide
  - Option: 19"-mounting-kit



### TECHNICAL PARAMETERS

Mobile Interface	LTE: 100 Mbps (DL) / 50 Mbps (UL) 3G: 42 Mbps (DL) / 5,76 Mbps (UL) 2G: 237 kbps (DL) / 59,2 kbps (UL)	
Temperature range	Function Storage	-40° C to + 70°C -40° C to + 85°C
Protection	IP30	
Supply voltage	9 to 36 VDC	
Consumption	Idel Transmission	2,3 W 5,5 W
Dimensions	Plastic box Metal box	51 x 87 x 116 mm (DIN 35 mm) 42 x 87 x 113 mm (DIN 35 mm)
Antenna connector	SMA – 50 Ohm	
User interface	2x ETH	Ethernet (10/100 Mbit/s)
Frequency bands	4G LTE: 800/900/1800/2100/2600 MHz UMTS/HSPA+: 900/1800/2100 MHz GSM/GPRS/EDGE: 900/1800 MHz	

Der Niederösterreichische  
Innovationspreis

